









Nozzle Heads for Rotating nozzle PRD 3500 for gun operation and manipulators

Z 20-2e

01.09.2016

	<p>Nozzle head complete DK1 Part no. 7027856 with protection plate</p> <p>min. 50 - max. 350 MPa min. 12,6 - max. 47,2 l/min</p> <p>for 6 nozzle inserts 3x on inner circle 3x on outer circle</p>	<p>Outer circle </p> <p>Inner circle</p> <p>f.e. removal of paint & coatings working width: 47 mm Distance: 30 mm</p>
	<p>Nozzle head complete DK2 Part no. 7027894 with protection plate</p> <p>min. 50 - max. 350 MPa min. 12,6 - max. 41,4 l/min</p> <p>for 6 nozzle inserts 3x on inner circle 3x on outer circle</p>	<p>Outer circle </p> <p>Inner circle</p> <p>z.B. surface cleaning working width: 47 mm Distance: 30 mm</p>
	<p>Nozzle head complete DK3 Part no. 7027895 with protection plate</p> <p>min. 50 - max. 350 MPa min. 9,7 - max. 29,1 l/min</p> <p>for 3 nozzle inserts on various nozzle circles</p>	 <p>f.e. removal of concrete working width: 67 mm distance: 30 mm</p>
	<p>Nozzle head complete DK4 Part no. 7027896 with protection plate</p> <p>min. 50 - max. 350 MPa min. 19,8 - max. 38,1 l/min</p> <p>for 3 nozzle inserts on various nozzle circles</p>	 <p>f.e. removal of paint & concrete working width: 55 mm distance: 30 mm</p>

Usable nozzle inserts Typ 0964

Required nozzle Ø by selection table depending from nozzle head

>>> see page Z 55-1e

>>> see page Z 20-3e up to Z 20-6e