

Straight Jet Insert Nozzles Form A + B

Z 41-1 e

13.11.2014

- For use with High Pressure Gun KSP 1200, Dump Gun 1500 and as insert for Rotating Nozzle PRD 1500 and Nozzle Carrier DT 2 + DT 4 of Tornado



Technische Daten

- Working pressure: max. 1500 bar
- Material: stainless steel 1.4034, hardened
- Sealing by means of O-Ring
- Nozzle factor: 0.95

Type	Nozzle Ø [mm]	L [mm]	Operating pressure [bar]	Part No.
A	0.50	12	1500	7001176
	0.60			7001177
	0.70			7001178
	0.80			7001179
	0.90			7003528
	1.00			7003529
	1.20			7003531
B	0.50	24		7014421
	0,60			xxx
	0,70			7014422
	0,80			7012688
	0,85			7014110
	0.90			7001180
	1.00			7001181
	1.10			7001182
	1.20			7001183
	1.30			7001184
	1.40			7001185
	1.50			7001186
	1.60			7001187
	1.70			7001188
	1.80		7001189	
	1.90		7001190	
	2.00		7001191	
2.10	7001192			
2.20	7001193			
2.30	7001194			
O-Ring				1060382

Additional nozzle diameters available on request