

Pipe Cleaning Nozzle Aqua Twister 1500 bar

rotating outer Ø 10 – 20 mm

Z 46-4e

01.01.2017

Drilled rotating nozzle of hardness steel with different jet angles for pipe cleaning in various industries.
For use with rigid lances or flexible hoses.







Part no.	Outer Ø mm	Length mm	Connection female	Type	min. – max. pipe inner Ø mm
7024243	10	46	M7	9010	15 - 30
7014072	12	48	G 1/8"	9012	20 - 40
7024244	16	51	G 1/8"	9016	25 - 60
7024245	18	56,5	G 1/4"	9018	30 - 100
7025140	20	60,5	G 1/4"	9020	35 - 120






Order example:

Part No. 7025140 – 5
Aqua Twister with G 1/4" f.
With jet angle no. 5
Type 9020-5

as well as indication of working pressure and flow rate of the used pump.



Jet angle No. Description		Jet angle
1	4 x 90°	
2	1 x 0° 4 x 90°	
3	2 x 90° 2 x 45°	
4	1 x 0° 2 x 90° 2 x 45°	
5	2 x 10° 2 x 90° 2 x 45°	
6	1 x 0° 2 x 10° 2 x 90° 2 x 45°	

Jet angle No. Description		Jet angle
7	4 x 45°	
8	1 x 0° 4 x 45°	
9	2 x 10° 4 x 45°	
10	1 x 0° 2 x 10° 4 x 45°	
11	2 x 10° 4 x 75°	
12	1 x 0° 2 x 10° 4 x 75°	