

## High Pressure Hose Lines

Z 60-3e

2500 / 3000 / 4000 bar

01.08.2017

### Component group includes:

- Hose line with fitting M 14x1.5 LH / M 18x1.5 LH / M 20x1.5 LH male
- Protective hose
- See page Z 60-4 e



### Technische Daten

- Working pressure: max. 2500 / 3000 / 4000 bar
- Hose inner layer: Polyoxymethylene (POM)
- Pressure hose section: 6 layers of steel wire of highest tensile strength
- Hose outer layer: Polyamide (PA)
- Fitting: High pressure fitting (steel) with 59° cone

ID [mm]	max. pressure	Outer diam. Hose Ø Sleeve Ø	Fitting male both ends	Bending radius [mm]	with protection hose Y / N	Length [m]	Part no.
5	2500 bar	13,0 mm 18,6 mm	M 14x1.5 LH	175	Y	5	7015603
						10	7006367
						15	7006368
						20	7006369
	3000 bar	13,3 mm 18,6 mm	M 14x1.5 LH	200	Y	20	7000471
	4000 bar	15,0 mm 19,6 mm	M 14x1.5 LH	200	N	5	7022328
Y					10	7027605	
					20	7020428	
8	2500 bar	17,2 mm 22,8 mm	M 14x1.5 LH	200	Y	10	7006370
						15	7006371
						20	7006372
	3000 bar	19,5 mm 24,0 mm	M 14x1.5 LH	250	Y	20	7000476

ID [mm]	max. pressure	Outer diam. Hose Ø Sleeve Ø	Fitting male both ends	Bending radius [mm]	with protection hose Y / N	Length [m]	Part no.
12	2500 bar	29,8 mm 33,8 mm	M 18x1.5 LH	350	Y	20	7017337
	3000 bar	29,9 mm 33,8 mm	M 20x1.5 LH	350	Y	20	7002976