


Orbital Nozzles KOD 500 - 2500 for gun operation

Z 40-1 e

01.04.2008



Technical data

Typ	max. l/min	max. bar	Outer Ø mm	Length mm	Nozzles / Rotor Ø [mm]	Weight kg	α	Connection female
KOD 500	48	500	43	109	1,90	0,65	30°	G 1/4" BSP
KOD 800	38	800	43	133	1,50	0,7	20°	G 3/8" BSP
KOD 1500 / 1000	35	1000	49	135	1,35	1,2	20°	G 3/8" BSP
KOD 1500	28	1500	49	135	1,10	1,2	20°	M14x1,5LH
KOD 2500	21	2500	49	135	0,85	1,3	20°	M14x1,5LH oder 9/16"UNF-LH

When ordering please state model and nozzle size or flow and operating pressure.
Further nozzle sizes and adapters to fit all standard lance thread types are available on request.

Applications

- Removal of concrete; laying bare reinforcements
- Cleaning and washing of concrete and stones

Note

When ordering nozzle inserts as replacements always make sure that the drive tube with O-ring matches the actual rotor size fitted in the nozzle (see page Z40-4e).

That means: If it is intended to order a nozzle insert which differs in size from the rotor in the nozzle in original condition, it is essential in such cases to also order the corresponding drive tube with O-ring (see page Z40-4e).