

HP - Spray Dump Gun 2500 with mechanical valve	Z 10-1 e
	01.05.2010

- HP - Gun with spray tube 750 mm, handle, hose connector M 14x1.5 LH, bypass tube 400 mm and nozzle holder for insert nozzles (without nozzle)



Part No. 7016690

Optional

- without spray tube, bypass tube and nozzle holder



Part No. 7016762

Additional equipment

- Shoulder support
- Initiator for remote control



Part No. 7009215

Part No. 7017928

Technical data

Max. working pressure:	2500 bar
Max. capacity:	30 l/min
Connection:	M 26x1.5 female (with pressure ring M 14x1.5 LH and pressure screw M 26x1.5)
Total length:	1000 mm
Weight:	approx. 3.4 kg complete approx. 3.1 kg without spray tube and bypass tube
Temperature:	max. 50°C
Usable nozzle inserts:	Insert nozzles Type 0952 (see page Z 45-1 e) Rotating nozzle PRD 4000 (see page Z 20-1 e) Orbital nozzle KOD 2500 (see page Z 40-1/2/3/4 e)

Applications

- For manual surface cleaning of all type of forms and materials with nozzle.



For hand-held operation of a spray gun the nozzle diameter must be selected to ensure that the reaction force in the longitudinal axis when used at the max. operating pressure does not exceed 250 N. If the reaction force is in excess of 150 N the gun must be equipped with a support, in compliance with the European Norm EN 1829.