

# DXO CARTRIDGE

The modern, eco-friendly solution to fluid conditioning.

## DXO Cartridge:

- Particle filtration to 0.1 micron
- Removal of:
  - Bacteria
  - Water (free and emulsified)
  - Oxidation products (Sludge and resin)
- Mitigation and reduction of varnish

## Benefits:

- Smart & effective maintenance system
- Cost reduction
- Enhanced lifetime service
- Minimised fluid oxidation
- Increased production
- Reduced oil changes
- Eco-friendly
- Easy service
- Small footprint



## Technical Specification:

### SINGLE DXO CARTRIDGE

Dry Weight	2,0 kgs
Contamination capacity	Up to 7 kg
Typical cartridge flow	1 lpm @ 32 cSt
Diameter	Ø186 mm
Height	264 mm
Recommended Reservoir Size	2000l @ 32cSt
Water absorption, free & bound	2600 ml
Temperature limits	Min 0°C. Max 100°C
Material cartridge	PP Cellulose mix
DXO Cartridge Box	1 PCS 192 x 192 x 270 mm, 2,2 kg



© 2019 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



**LONGWALL HYDRAULICS**  
 NSW 02 4271 2999 - QLD 07 4952 3612  
[www.longwall.net](http://www.longwall.net)