

High Pressure Filter

Z 61-1 e

1500 / 2500 bar

01.04.2008

Design

- Stainless steel housing without filter insert
- Reworkable, metal-to-metal sealing system
- Transparent spray protection
- FDA/GMP suitability

Fluids

- Water, saline and demineralized
- Non-aggressive chemical fluids
- Biotechnological suspensions
- Solutions (e.g. acetone)
- Viscosity up to 2000 mPas



Max. working pressure 1500 bar Part No. 7010825
 Max. working pressure 2500 bar Part No. 7011380

German Patent 10224634 granted and
 Foreign Patents applied for

Technical data

Max. flow (water)	50 l/min
Max. temperature	150°C
Max. differential pressure	150 bar
Total length	205 mm
Outer diameter	150 mm
Connection	M 26x1.5
(autoclave hp-fitting with pressure ring M 14x1.5 LH and pressure screw M 26x1.5)	
Weight	14.6 kg

Applications

- High pressure filtration, nozzle and valve protection in process plants and on high pressure jetting installations

Filter inserts

Available, reusable, washable filter inserts in stainless steel

- 10 µm Part No. 7011321
- 25 µm Part No. 7011322
- 50 µm Part No. 7009953
- 100 µm Part No. 7009954
- 200 µm Part No. 7010298

